Docket No.: 0399-0130PUS1

Art Unit: 3634

Page 2 of 10

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A security door apparatus for an entrance door that is openable and closable with respect to one side of a door opening frame, the security door apparatus comprising:

an entrance door;

an upper horizontal slide guide or a lower horizontal slide guide disposed on one of an inner side of the entrance door or on a side of the door opening frame;

a rectangular-shaped auxiliary door having a width that is smaller than a width of the entrance door, the auxiliary door having a first side connected to the horizontal slide guide disposed on the one of a side the inner side of the entrance door or the door frame opening frame, and a second side connected to the one a side of the entrance door or the door opening frame not having the horizontal slide guide,

wherein the auxiliary door is mounted on the <u>entrance</u> door and the door opening frame so that, and when the <u>entrance</u> door is opened, the auxiliary door forms a barrier across an opening between the <u>entrance</u> door and the door opening frame; and

wherein the auxiliary door has multiple openings formed so that a receiver person inside the <u>auxiliary</u> door can visually confirm an <u>identify identity</u>-of <u>a another</u> person outside of the <u>auxiliary</u> door through the openings in the <u>auxiliary</u> door.

Application No. 10/807,586
Amendment filed May 19, 2006

Reply to Office Action of March 9, 2006

Docket No.: 0399-0130PUS1 Art Unit: 3634

Page 3 of 10

2. (Currently Amended) The security door apparatus according to Claim 1,

wherein an upper and a lower corner on the first side of the auxiliary door are rotatably

connected to the entrance door and an upper and a lower corner on the second side of

the auxiliary door are rotabably connected to the door opening frame, and

wherein one of the first side or the second side of the auxiliary door is slidable

with respect to the horizontal slide guide disposed on either the entrance door or the

door opening frame, thus enabling the slidable side of the auxiliary door to be opened

and closed when the entrance door is opened and closed.

3. (Currently Amended) The security door apparatus according to Claim 2,

wherein one of the first side or the second side of the auxiliary door is detachably

mounted on one of the entrance door or or the door opening frame.

4. (Currently Amended) The security door apparatus according to Claim 3,

further comprising:

upper and lower locking bearing parts provided on both the entrance door and

the door opening frame; and

axial support parts provided at the four corners of the auxiliary door,

Application No. 10/807,586
Amendment filed May 19, 2006

Reply to Office Action of March 9, 2006

Docket No.: 0399-0130PUS1 Art Unit: 3634

Page 4 of 10

wherein the axial support parts on one of the first side and second side of the

auxiliary door are detachably mounted to the locking bearing parts on the door opening

frame or the the door, and

wherein the axial support parts formed on the other of the first and second side of

the auxiliary door are slidably attached to the horizontal slide guides guide.

5. (Currently Amended) The security door apparatus according to Claim 3,

further comprising

a notch provided on each of the first side and the second sides side of the

auxiliary door, the notches being provided so that the auxiliary door does not make

contact with a door lock knob of the entrance door when the auxiliary door is in open and

closed positions.

6. (Currently Amended) The security door apparatus according to Claim 3,

wherein the openings are formed in an upper half part of the auxiliary door,

the openings having a louver-shape structure through which a receiver the person

inside the auxiliary door can confirm the an identify of a of the person on the

opposite side of outside the auxiliary door.

7. (Cancelled)

JMS/CTT/eb

Application No. 10/807,586 Amendment filed May 19, 2006

Reply to Office Action of March 9, 2006

Docket No.: 0399-0130PUS1

Art Unit: 3634

Page 5 of 10

8. (Currently Amended) The security door apparatus according to Claim 4 claim

1, wherein the auxiliary door is provided with a rectangular-shaped window that can

be opened and closed, the window being disposed below the multiple openings one

side end part of the auxiliary door is attachably and detachably provided at one side end

part of the door or at one side end part of the door opening frame, a width of the auxiliary

door is formed slightly larger than the width of a delivered package for a door-to-door

delivery, etc., and this auxiliary door partially is provided with openably and closably an

opening and closing window through which the package is received.

9. (Cancelled)

10. (Cancelled)

JMS/CTT/eb